Plasma CUTTER 35KF



EN 60974-1

10 **≥** 35A

Will cut up to 12mm Internal air compressor Single phase 230V (+/-15%)

Ideal for maintenance work, the CUTTER 35KF is benefits from Inverter technology.

Internal air compressor

With its internal compressor, the plasma 35KF does not require an external supply of compressed air.

Quality cutting without distortion

The plasma 35KF allows high quality cutting even on painting surfaces:

- ✓ Up to 12mm steel, stainless steel and cast iron.
- ✓ Up to 8mm aluminium and copper.

No HF Start

With the « Pilot Arc » system, the arc starts without having any contact with the welding sheet. Starting without HF avoids any electromagnetic interference (radio, computers, phones, medical equipment, etc...).

Easy to use, fast and safe

- Torch: 4m with safety trigger to avoid accidental start.
- Internal compressor (noise): 60/70 Db.
- Reinforced protection for the use with generators and against permanent overvoltage up to 400V (factory tested).
- PFC feature: Power factor correction: regulates and uses the power supply more efficiently.



Ref. 031036







♪/≗ AIR SYSTEM EN 60974-1 (40°C) Clean cut Iэ Presure L/mm Kompressor cm/kg X_{% l2 max} I_{A (60%)} 50/60Hz inside 28x52x46 8 kW 10 kVA 230V 1~ 16A 10-35 30 included 28 /30

29/11/2013 MADE in FRANCE www.gys.fr



บริษัท จันทร์เกษมอินเตอร์เนทชั่นแนล จำกัด

90 ถนนแจ้งวัฒนะ ซอย12 เขตหลักสี กรุงเทพฯ 10210

ฝ่ายขาย : โทร. 0 2982 7000, 0 2984 3244 แฟกซ์ : 0 2982 7770 ฝ่ายบริการ : โทร. 0 2982 7000, 0 2982 5381 แฟกซ์ : 0 2982 4687 E-mail : sales@chankaseminter.com, www.chankaseminter.com